

# Lessons Learned and Present Day Challenges of Addressing 20<sup>th</sup> Century Radiation Legacies of Russia and the United States

**BEST AVAILABLE COPY**

Prepared for the U.S. Department of Energy  
Assistant Secretary for Environmental Management

**CH2MHILL**

*Hanford Group, Inc.*

Richland, Washington

Contractor for the U.S. Department of Energy  
Office of River Protection under Contract DE-AC06-99RL14047

---

Copyright License By acceptance of this article, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper

Approved for Public Release; Further Dissemination Unlimited

### INFORMATION CLEARANCE FORM

<p><b>A. Information Category</b></p> <input checked="" type="checkbox"/> Abstract <input type="checkbox"/> Journal Article <input type="checkbox"/> Summary <input type="checkbox"/> Internet <input type="checkbox"/> Visual Aid <input type="checkbox"/> Software <input type="checkbox"/> Full Paper <input type="checkbox"/> Report <input type="checkbox"/> Other _____	<p><b>B. Document Number</b> <u>N/A RPP-7267-FP</u></p> <p><b>C. Title</b>                  Lessons Learned and Present Day Challenges of Addressing 20th Century Radiation Legacies of Russia and the United States</p> <p><b>D. Internet Address</b></p>
---	--

<p><b>E. Required Information</b></p> <p>1. Is document potentially Classified? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes (MANDATORY)                  _____                  Manager's Signature Required</p> <p>If Yes _____ <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes Classified                  ADC Signature Required</p> <p>2. Internal Review Required? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes                  If Yes, Document Signatures Below                  Counsel: _____                  Program: _____</p> <p>3. References in the Information are Applied Technology <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes                  Export Controlled Information <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes</p>	<p>4. Does Information Contain the Following? (MANDATORY)</p> <p>a. New or Novel (Patentable) Subject Matter? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes                  If "Yes", Disclosure No.: _____</p> <p>b. Information Received in Confidence, Such as Proprietary and/or Invention? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes                  If "Yes", Affix Appropriate Legends/Notices.</p> <p>c. Copyrights? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes      If "Yes", Attach Permission.</p> <p>d. Trademarks? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes      If "Yes", Identify in Document.</p> <p>5. Is Information requiring submission to OSTI? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes                  If Yes UC- _____ and B&amp;R- _____</p> <p>6. Release Level? <input checked="" type="checkbox"/> Public <input type="checkbox"/> Limited</p> <p>7. Charge Code _____ <u>HFLH0321</u></p>
--	--

**F. Complete for a Journal Article**

1. Title of Journal \_\_\_\_\_

**G. Complete for a Presentation**

1. Title for Conference or Meeting International Conference on "Radiation Legacy of the 20th Century"

2. Group Sponsoring The Ministry of the Russian Federation for Atomic Energy (MINATOM)

3. Date of Conference 10/30/00

4. City/State Moscow, Russia

5. Will Information be Published in Proceedings?  No  Yes


6. Will Material be Handed Out?  No  Yes

<p><b>H. Author/Requestor</b></p> <p><u>J. G. Kristofzski</u>                  (Print and Sign) _____</p>	<p><b>Responsible Manager</b></p> <p><u>J. G. Kristofzski</u>                  (Print and Sign) _____</p>
---	---

I. Reviewer's	Yes	Print	Signature	Public Y/N (If N, complete J)
General Counsel	<input checked="" type="checkbox"/>	<u>S. C. Bensussen</u>	<u>[Signature]</u>	<u>Y</u> / N
Office of External Affairs	<input checked="" type="checkbox"/>	<u>A. C. Etheridge</u>	<u>[Signature]</u>	<u>Y</u> / N
DOE-RL (for Hanford only)	<input checked="" type="checkbox"/>	<u>D. C. Bryson</u>	<u>[Signature]</u>	<u>Y</u> / N
Other	<input type="checkbox"/>	_____	_____	Y / N
Other	<input type="checkbox"/>	_____	_____	Y / N

**J. If Information Includes Sensitive Information and is not to be released to the Public indicate category below.**

<input type="checkbox"/> Applied Technology	<input type="checkbox"/> Protected CRADA
<input type="checkbox"/> Personal/Private	<input type="checkbox"/> Export Controlled
<input type="checkbox"/> Proprietary	<input type="checkbox"/> Procurement Sensitive
<input type="checkbox"/> Business Sensitive	<input type="checkbox"/> Patentable
<input type="checkbox"/> Predecisional	<input type="checkbox"/> Other (Specify) _____
<input type="checkbox"/> UCN	



**K. If Additional Comments, Please Attach Separate Sheet**

#### LEGAL DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced from the best available copy.

Printed in the United States of America

# Lessons Learned and Present Day Challenges of Addressing 20<sup>th</sup> Century Radiation Legacies of Russia and the United States

Authored by:  
N. P. Laverov  
I. Velichkin  
Russian Academy of Sciences

A. A. Iskra  
V. V. Shatalov  
All-Russian Science and Research Institute for  
Chemical Technologies and the Russian  
Federation Ministry of Nuclear Energy

Date Published  
October 2000

E. G. Drozhko  
Mayak Industrial Association

O. G. Lebedev  
V. K. Popov  
Russian Scientific Center, Kurchatov Institute

M. T. Rengel  
J. G. Kristofzski  
A. L. Schubert  
CHG2M HILL Companies Ltd.; USA

To Be Presented at  
International Conference on "Radiation Legacy of the 20<sup>th</sup> Century"  
Moscow, Russia  
October 30 to November 3, 2000

Sponsor  
The Ministry of the Russian Federation for Atomic Energy (MINATOM)

Prepared for the U.S. Department of Energy  
Assistant Secretary for Environmental Management

**CH2MHILL**  
*Hanford Group, Inc.*

P. O. Box 1500  
Richland, Washington

Contractor for the U.S. Department of Energy  
Office of River Protection under Contract DE-AC06-99RL14047

---

**Copyright License** By acceptance of this article, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper

Approved for Public Release; Further Dissemination Unlimited

**LESSONS LEARNED AND PRESENT DAY CHALLENGES OF  
ADDRESSING 20<sup>TH</sup> CENTURY RADIATION LEGACIES OF  
RUSSIA AND THE UNITED STATES**

**Submitted by:**

All-Russian Science and Research Institute for Chemical Technologies  
and  
CH2M HILL Companies Ltd.

**Authored by:**

N.P. Laverov, I. Velichkin; Russian Academy of Sciences  
A.A. Iskra, V.V. Shatalov; All-Russian Science and Research Institute for Chemical  
Technologies and the Russian Federation Ministry of Nuclear Energy  
E.G. Drozhko; Mayak Industrial Association  
O.G. Lebedev, V.K. Popov; Russian Scientific Center, Kurchatov Institute  
M.T. Rengel, J.G. Kristofzski, and A.L. Schubert; CH2M HILL Companies Ltd.; USA

**International Conference on:  
Radiation Legacy of the 20<sup>th</sup> Century: Environmental Restoration**

**30 October to 3 November 2000  
Moscow, Russian Federation**

## **INTRODUCTION**

The decommissioning of nuclear submarines, disposal of highly-enriched uranium and weapons-grade plutonium, and processing of high-level radioactive wastes represent the most challenging issues facing the cleanup of 20<sup>th</sup> century radiation legacy wastes and facilities. The United States and Russia are the two primary countries dealing with these challenges, because most of the world's fissile inventory is being processed and stored at multiple industrial sites and nuclear weapons production facilities in these countries.

### **ARRICT**

As part of the Russian Federation, Federal Target Program – Radioactive Wastes and Nuclear Materials Handling, Recycling, and Disposal in 1996-2005, an effort was undertaken to backfill Lake Karachai and to vitrify and grade high-level wastes at the Mayak Industrial Association.

*Please add additional introductory information on ARRICT here.*

### **CH2M HILL Companies, Ltd.**

CH2M HILL is a global project delivery firm providing integrated services to public and private clients in the fields of energy and nuclear management, water, environmental management and site restoration, transportation, industrial facilities, and related infrastructure. CH2M HILL's services encompass all phases of project development and delivery, from planning and financing through design, construction, operations and maintenance, and long-term sustainable development. Through a global network of 153 offices and more than 10,000 professional staff worldwide, CH2M HILL provides local resources to clients wherever they operate.

CH2M HILL is currently managing two of the most important nuclear projects being conducted by the U.S. Department of Energy (DOE). At the Rocky Flats Environmental Technology Site, CH2M HILL is directing the first environmental cleanup and closure of a former U.S. DOE nuclear weapons production site. At the DOE Hanford Site, CH2M HILL is implementing a strategy to eliminate the hazards and public health risks associated with storing millions of gallons of high-level radioactive liquid waste.

## **TECHNICAL ACCOMPLISHMENTS**

### **Lake Karachai Remediation**

Since 1951, Lake Karachai, a natural drainless reservoir in Russia, was used to stockpile liquid mid-level wastes. During the period of active use, a total of 120 million curies were discharged into the lake. In 1988, a phased project to eliminate the reservoir began with confining radioactive bottom sediments into box-shaped reinforced concrete blocks. The lake was then filled with porous material capable of absorbing groundwater during flooding. The final phase of the project involved filling the lake with rock. This remediation work resulted in a reduction of the surface area of the lake from 222,000 square meters in 1991 to 120,000 square meters in 1999, thereby substantially decreasing aeoliation of radioactive aerosols from the surface and water front. Currently, the work is approaching its completion stage.

Since 1992, an investigation has been underway to determine patterns of contaminated water migration originating in Lake Karachai. This investigation involved a detailed survey of the geological structure of the Mayak site and determination of the lithosphere structure to a depth of 5 kilometers. Based on the results of the survey, short- and long-term forecasts of pollution migration were made, and sites for underground laboratory and future repositories for radioactive wastes are being selected.

### **Mayak Vitrification Project**

Personnel at the Mayak Industrial Association have implemented a technology to vitrify high-level liquid wastes in EP-500 ceramic kilns. The aggregate radioactivity of the processed wastes has reached 150 million curies. Borophosphate glass has been developed and tested for further use in vitrification of high-level wastes. A scheme has been designed to prepare high-level wastes for inclusion in borophosphate glass. An additional industrial facility has been proposed to enable the processing of different types of high-level wastes as borosilicate and quasi-mineral compositions. Within the next twelve years, Mayak personnel are planning to implement a technology to grade high-level wastes and to extract cesium, strontium, transuranium, and rare-earth elements to substantially change the composition and quality of vitrified high-level wastes. Implementation of this technology will enable the storage and disposal of each fraction of fissile material based on the quantity of material and its radiotoxicity period. In addition, the plant will be processing and vitrifying the entire range of high- and mid-level wastes generated at Russia's radiochemical and radioisotope plants.

### **Hanford River Protection Project**

CH2M HILL is managing 200 million liters of highly radioactive and hazardous waste stored in 177 underground tanks at the U.S. DOE Hanford Site. This liquid waste represents 60 percent of the United States' high-level radioactive waste inventory. The ultimate goal of this project is to vitrify the waste into glass logs to be stored in a long-term underground repository. CH2M HILL is removing liquid waste from ~~the tanks~~ tanks, minimizing the risk ~~of flammable gas~~ flammable gas buildup in certain tanks, and resolving significant safety issues to remove nearly 20 tanks from the U.S. Congressional watch list of dangerous tanks. These risk reduction activities involve rotary core sampling of hard-caked waste deposits, tank sluicing and sludge removal for high heat tanks, a comprehensive upgrade of existing tank farm infrastructure, and technology deployment and new equipment installation for retrieval and transfer of the liquid waste to a vitrification facility.

CH2M HILL is addressing the nation's legacy of nuclear wastes by creating first-of-a-kind approaches to deal with the challenges. For instance, the C-106 tank at the Hanford tank farm is a single-shell tank that has been a safety concern for several years because of its high heat content. The physical characteristics of the waste in this tank result in both liquid and solid wastes. There was sufficient heat content in the tank that if left alone, the temperature would rise, which had the potential to cause a catastrophic failure of the tank. CH2M HILL managed the temperature by adding water to the single-shell tank for evaporative cooling and installing a sluicing system in the tank. The waste was ~~sluiced~~ to a safer double-shell tank, eliminating the risk the tank once posed.

CH2M HILL also resolved the issues of the SY-101 double-shell tank, once considered the most dangerous tank in the DOE complex. This tank generated and retained significant quantities of flammable gas made up of hydrogen and ammonia, which presented the potential for explosion. To remedy the situation, a mixer pump was installed in 1993 to stir the tank waste, which resulted in the safe and gradual release of the built up flammable gases. Recently, the tank began retaining additional quantities of flammable gas, demonstrating that another solution was needed. Having studied the tank's physical properties, CH2M HILL understood them well enough to suggest that diluting the waste with water and transferring it to other tanks would resolve the issue. Now that this work is complete, the tank is no longer considered the most dangerous tank in the DOE complex.

### **Rocky Flats Closure Project**

CH2M HILL is deactivating, decommissioning, decontaminating, and demolishing more than 700 facilities totaling 325,150 square meters of former nuclear weapons production facilities at the U.S. DOE Rocky Flats Site. For this ten-year project scheduled to be completed by December 15, 2006, CH2M HILL is applying plasma arc equipment dismantlement techniques, pipe-and-go contaminated waste packaging, and inner tent worker protection technologies. In addition, several methods have been developed to process and package more than 115,000 kilograms of plutonium residue waste. Over the course of the project, CH2M HILL will dispose of more than 200,000 cubic meters of transuranic and low-level waste and will remediate more than 130 individual areas of soil and water contamination at the site.

Rocky Flats stores more than 115,000 kilograms of plutonium byproducts of past nuclear weapons production operations. Called residues, these wastes must be stabilized and/or repackaged prior to offsite shipment. Most of the Rocky Flats residues will be disposed at the DOE Waste Isolation Pilot Plant in Carlsbad, New Mexico, a long-term radioactive waste repository. Residues are in the form of salt, ash, and wet and dry combustibles. One device that had an incredible effect on the residues program was the development and use of the pipe overpack component. Designed at Rocky Flats, the pipe overpack component is a .635-millimeter thick stainless steel pipe that holds two waste containers. The pipe is packed into a 208.197-liter drum and shipped for disposal. Because of the shielding the pipe overpack component provides within the waste drum, many residues do not require the stabilization once necessary. This technology has reduced worker exposure, increased safety, and saved valuable time and cost. To date, CH2M HILL has processed and packaged more than 60,000 kilograms of Rocky Flats residues.

CH2M HILL applies the latest and most effective technologies for decontaminating nuclear facilities and reducing the hazardous waste volume generated by decommissioning activities. Many nuclear buildings consist of reinforced-concrete walls that are several feet thick. These thick walls add a layer of complexity to the deactivation and decommissioning process. In late 1999, CH2M HILL directed the deactivation and decommissioning of a large plutonium building at Rocky Flats. The building cluster included Building 779, a former nuclear weapons research and development facility, and its surrounding support structures. In all, nearly 1 hectare of building space was deactivated, decontaminated, and demolished. CH2M HILL used innovative techniques including a high-pressure water spray called hydrolasing to remove surface contamination from concrete and a special survey machine that can assess 1.829-meter-wide

stretches of wall or floor at a time. To determine that the building was ready for demolition, CH2M HILL performed more than 2 million separate radiation measurements.

## **TECHNICAL CHALLENGES**

### **Technology Challenges**

For the Hanford River Protection Project, many technology hurdles must be overcome to achieve the safe, compliant, and cost-effective retrieval, vitrification, and long-term storage of the high-level radioactive waste in the massive Hanford tank farm. CH2M HILL is continually collaborating with several United States technology vendors to identify and deploy technology. Through participation in the October, International Conference and other initiatives, CH2M HILL hopes to exchange technology information and foster a working relationship with the Russian Federation to further the technological development required to deal with the radiation legacy of the 20<sup>th</sup> century.

The Hanford River Protection Project requires technology or technical process development for the areas presented below.

### **Large-scale Vitrification Systems**

Vitrification systems are being successfully demonstrated at DOE sites in the United States and commercially in Europe. The unique challenges at Hanford relate to designing scaled-up units that can handle Hanford's large volume of ~~high-level~~ radioactive wastes. Pretreatment technologies involve ion exchange systems to remove cesium-90 and technetium-99, precipitation systems to remove strontium-90 and transuranic, and ultra-filtration systems to separate solids from aqueous wastes.

### **Curie Count**

Currently, techniques to assess the amount of residuals left in a tank exist. However, techniques must be developed to determine the amount of curies left in a tank. CH2M HILL will need this capability within a few years.

### **Sludge Mobilization Methods**

An enhanced sludge mobilization method is needed to retrieve sludge that is beyond the effective cleaning radius of a baseline pair of long-shaft mixer pumps. The objective for this method development is a small system that can be installed in a tank along with a mixer, when mobilization is required to retrieve remaining sludge in a tank.

### **Variable Level Suction Transfer Pump**

A variable level suction transfer pump is needed to draw waste from pre-selected levels that range from the surface of the waste to within 25.4 centimeters of the bottom of a tank ~~\_\_\_\_\_~~. Currently, transfer pumps achieve variable suction levels by using a flexible hose controlled by a tether cable. This design cannot be operated simultaneously with mixer pumps because of hose instability.

### Pressure and Velocity Determination

Inter-area transport lines for particulate slurries have become plugged in the past due to particle settling, phase changes, or reactions accompanied by precipitation or gel formation that occurred during transport. Information to predict pressure drop and critical transport velocity of wastes with known properties is required to ensure that wastes can be safely transported without risk of plugging. To minimize the dilution required to modify waste properties, methods to predict the effect of dilution, washing, or leaching on the slurry properties is also required. Dilution both increases the volume of the waste and has negative implications for tank waste management both from a space perspective and for settling and separation of solids. Waste compatibility is also an issue in the case of blending of wastes from several simultaneous or sequential retrievals.

### Waste Solubility

Information is needed on the solubility of various components in the complex solid and liquid matrices of the Hanford tank wastes, especially those associated with sludges. CH2M HILL needs to predict when solids will precipitate or when gels will form in retrieval, wash, and leach solutions. Empirical water wash and caustic leach data from enhanced sludge wash testing of tank sludge samples and other data from dissolution testing of saltcake samples must be supplemented.

### Precipitation Model

Predicting the precipitation of solids in a complex, concentrated brine requires a suitable model and a well-designed set of data from which model parameters can be obtained. Although the identity and approximate quantities of major and minor chemical components in the Hanford tanks are fairly well defined, there are inadequate fundamental experimental data to support an adequate predictive model, and there has been inadequate use of existing data. The solubilities of solid phases in high-ionic strength brines that approximate subsets of the actual Hanford chemical systems need to be measured to include: 1) determine equilibrium constants and 2) extract electrolyte model parameters describing the behavior of sparingly soluble compounds.

### Contaminant Release Compliance

In order to meet the contaminant release specifications for the disposal of low-activity tank waste, radiocontaminants are physically trapped in glass. However, only a few of these radioelements drive the performance assessment. If key radioelements could be chemically trapped after release from glass, the performance of the waste disposal system could be significantly improved. Hydraulic properties of getter materials (original, loaded, and discharged) need to be measured to fully understand waste disposal performance in the presence of getters. The use of getter materials in the DOE Savannah River Site's disposal of the saltstone waste was an important consideration in the approval of that site's tank waste disposal strategy.

### Sluicing Systems

Improvements in sluicing technology have been made since past practice sluicing was performed at Hanford for tank waste retrieval. A better understanding of these improvements and how they compare to past practice sluicing is needed to optimize waste retrieval operations. A direct comparison between past practice sluice nozzles and current industrial nozzles needs to be performed to provide the most effective design to support high-level waste feed to the

vitrification plant. A comparison between past practice pumping systems and current improved pumping systems should also be completed. The comparisons must provide a clear quantitative analysis of the ability of each nozzle and pump type configuration and the ability to move different waste types.

#### Leakage Detection Systems

The use of past-practice sluicing for single-shell tank waste removal involves the addition of liquid to tanks and, therefore, increases the potential for waste leakage to the environment. Leak detection methods are needed that can signal and quantify a leak from a tank when only a small amount of waste has been released.

CH2M HILL must develop leak detection methods that will work in dry soils, be robust enough to handle a range of contamination levels, and will provide real time monitoring to support corrective actions during operations activities.

#### Vadose Zone Characterization

Alternative technologies to conventional core drilling for characterization of the vadose zone that are fast, economical, and minimize intrusion to the vadose zone are needed. These technologies should: 1) qualitatively and semi-quantitatively screen the soil column for contaminants of potential concern and in so doing identify zones of contamination in the tank backfill material and vadose zone in tank farm and 2) obtain soil samples at selected depths for confirmatory laboratory analysis. The technology must be capable to detect metal pipes and obstructions and selectively seal any borings introduced into the soil column to eliminate any potential pathway for contaminant leakage to the aquifer. Technology to verify the quantity and extent of contaminants leaked to the vadose zone in the tank farm will reduce the uncertainty associated with estimates of the radionuclide and hazardous chemical inventory in the tank farm soils. This information is key input to the performance assessment model and the assessment of alternatives for retrieval and tank farm closure.

#### Contaminant Containment

\_\_\_\_\_ of the 149 single-shell tanks at Hanford are known or suspected leakers. Retrieval of waste from these tanks will incur additional risk from leakage. In addition, waste that has been retrieved will be processed, vitrified, and disposed in solid form. Based on past analyses, this waste may add radionuclides to the soil column. For example, the performance assessment activities supporting the disposal of vitrified low-activity waste identified technetium-99 and selenium-79 as the radionuclides that contributed most significantly to long-term risk. If these key radioactive elements could be trapped or immobilized in the waste matrix, disposal facility, closed tanks, and/or the soil column, the risk to human health and the environment could be significantly reduced. It is proposed that sequestering agents be deployed as a permeable flow-through (reactive) barrier to attenuate the migration of these contaminants and reduce the risk. In the case of contaminated soil, the reactive barrier will be placed using conventional emplacement technology, e.g., slant drilling, etc. For the vitrified waste and for tank closure, it is proposed that the getter could be placed inside the facility.

## Regulatory Challenges

Russian and United States environmental programs are governed by regulatory agencies that oversee the work performed to cleanup the radioactive legacy of the 20<sup>th</sup> century. Both countries' programs are briefly described below.

### Russian Federation

The Russian Federation Nuclear Ministry's environmental and sustainable development programs and action plans are targeted to preserve fresh water quality, implement safe and environmentally sound practices for handling toxic and radioactive wastes, eliminate radioactive contamination, and foster sustainable development of Russian regions. These programs and plans are implemented on the basis of the most advanced technologies and reliable baseline environmental information collected and accumulated in various information systems.

In the Russian Federation, radiation legacy research included the development of information systems to collect and analyze reliable data that is important to assessing public health and environmental impacts of radioactive wastes. The Russian Federal Nuclear Ministry, Russian Academy of Sciences, Russian Federal Defense Ministry, Russian Public Health Ministry, Russian Federation Ministry for Natural Resources, Russian Federation Committee for Meteorology, and Russian Scientific Center – Kurchatov Institute worked together to develop the Radleg Information System. From 1995 to 2000, these organizations performed a comprehensive analysis of Russia's radiation legacy and created the system with a geoinformation center as part of International Science and Technical Center Project No. 245. A panel of Russian experts representing 25 organizations will use the Radleg Information System to evaluate environmental hazards and public health risks associated with the following:

- nuclear submarine decommissioning (unloading, transportation, and storage of irradiated fuel; dismantlement and removal of nuclear submarine parts; and handling of radioactive wastes)
- high-level uranium processing (processing into low-level uranium [to be used as fuel at nuclear power stations], transportation, and storage)
- weapons-grade plutonium processing (irradiation in light-water and fast reactors; production of MOX fuel; processing, transportation, and storage of MOX fuel; and waste handling, transportation, and storage).

### United States

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

[Faint, illegible text from a previous page or bleed-through, appearing as ghosting on lined paper.]

Environmental stewardship is a key element in the closure of the Rocky Flats site which in itself is one of the most important environmental projects in the entire United States. CH2M HILL strives to go beyond compliance to achieve environmental stewardship excellence that encompass a broad spectrum of activities at Rocky Flats that include: environmental monitoring; ecology and natural resource protection; natural resource conservation; recycling and waste reduction; environmental compliance; and soil, waste, and building remediation.

A unique regulatory strategy has been developed for Rocky Flats that focuses regulator attention on public protection and worker safety excellence, reducing the site's highest risks first, and removing the entire special nuclear material inventory from the site. CH2M HILL is working in partnership with the U.S. Environmental Protection Agency, the Colorado Department Public Health and Environment, and the U.S. Defense Nuclear Facilities Safety Board to completely eliminate all hazards at the site, demolish all facilities, and return the property to a natural open prairie indigenous to the Colorado area. Soil, water, and building remediation activities at Rocky Flats support the site's accelerated closure goal and are governed by the Rocky Flats Cleanup

Agreement. This agreement, signed by DOE, the Environmental Protection Agency, and the Colorado Department of Public Health and Environment in July 1996, provides the regulatory framework for closure with priority given to addressing the most urgent risks first.

## **RUSSIAN / UNITED STATES KNOWLEDGE TRANSFER**

Discussions are underway to launch joint Russian-American initiatives to share lessons learned from nuclear programs in Russia and the United States. These collaborative efforts may include comparative studies of environmental and public health impacts from high-level waste vitrification and grading processes in both countries. Comprehensive research will continue between the years 2000 and 2003 on the RADSITE project, which involves a coordinated approach among the Russian Federation; European Union; and the countries of Japan, China, India, and the United States.