


1 of 1

Date Received: B/2/93 KMB		INFORMATION RELEASE REQUEST		Reference: WHC-CM-3-4																																																																			
Complete for all Types of Release																																																																							
Purpose			ID Number (include revision, volume, etc.)																																																																				
<input type="checkbox"/> Speech or Presentation <input type="checkbox"/> Full Paper (Check only one suffix) <input type="checkbox"/> Summary <input type="checkbox"/> Abstract <input type="checkbox"/> Visual Aid <input type="checkbox"/> Speakers Bureau <input type="checkbox"/> Poster Session <input type="checkbox"/> Videotape			<input type="checkbox"/> Reference <input checked="" type="checkbox"/> Technical Report <input type="checkbox"/> Thesis or Dissertation <input type="checkbox"/> Manual <input type="checkbox"/> Brochure/Flier <input type="checkbox"/> Software/Database <input type="checkbox"/> Controlled Document <input type="checkbox"/> Other																																																																				
			WHC-EP-0599, Revision 0																																																																				
			List attachments.																																																																				
			N/A																																																																				
			Date Release Required																																																																				
			7-30-93																																																																				
Title The Role of Aging in Resolving the Ferrocyanide Safety Issue				Unclassified Category																																																																			
				Impact Level 4																																																																			
New or novel (patentable) subject matter? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If "Yes", has disclosure been submitted by WHC or other company? <input type="checkbox"/> No <input type="checkbox"/> Yes Disclosure No(s).			Information received from others in confidence, such as proprietary data, trade secrets, and/or inventions? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes (Identify)																																																																				
Copyrights? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If "Yes", has written permission been granted? <input type="checkbox"/> No <input type="checkbox"/> Yes (Attach Permission)			Trademarks? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes (Identify)																																																																				
Complete for Speech or Presentation																																																																							
Title of Conference or Meeting N/A			Group or Society Sponsoring																																																																				
Date(s) of Conference or Meeting		City/State		Will proceedings be published? <input type="checkbox"/> Yes <input type="checkbox"/> No Will material be handed out? <input type="checkbox"/> Yes <input type="checkbox"/> No																																																																			
Title of Journal																																																																							
CHECKLIST FOR SIGNATORIES																																																																							
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Review Required per WHC-CM-3-4</th> <th style="text-align: center;">Yes</th> <th style="text-align: center;">No</th> <th style="text-align: left;">Reviewer - Signature</th> <th style="text-align: left;">Indicates Approval</th> <th style="text-align: left;">Date</th> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;"><u>Name (printed)</u></td> <td style="text-align: center;"><u>Signature</u></td> <td></td> </tr> </thead> <tbody> <tr> <td>Classification/Unclassified Controlled Nuclear Information</td> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Patent - General Counsel</td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td>S. W. Berglin</td> <td></td> <td>8/2/93</td> </tr> <tr> <td>Legal - General Counsel</td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td>S. W. Berglin</td> <td></td> <td></td> </tr> <tr> <td>Applied Technology/Export Controlled Information or International Program</td> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td></td> <td></td> <td></td> </tr> <tr> <td>WHC Program/Project</td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td>R. J. Cash</td> <td></td> <td>7-27-93</td> </tr> <tr> <td>Communications</td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td>W. P. Whiting</td> <td></td> <td>5/4/93</td> </tr> <tr> <td>RL Program/Project</td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td>R. F. Christensen</td> <td></td> <td>8-4-93</td> </tr> <tr> <td>Publication Services</td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td style="text-align: center;"><input type="checkbox"/></td> <td>C. J. Forbes</td> <td></td> <td>8/9/93</td> </tr> <tr> <td>Other Program/Project</td> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						Review Required per WHC-CM-3-4	Yes	No	Reviewer - Signature	Indicates Approval	Date				<u>Name (printed)</u>	<u>Signature</u>		Classification/Unclassified Controlled Nuclear Information	<input type="checkbox"/>	<input checked="" type="checkbox"/>				Patent - General Counsel	<input checked="" type="checkbox"/>	<input type="checkbox"/>	S. W. Berglin		8/2/93	Legal - General Counsel	<input checked="" type="checkbox"/>	<input type="checkbox"/>	S. W. Berglin			Applied Technology/Export Controlled Information or International Program	<input type="checkbox"/>	<input checked="" type="checkbox"/>				WHC Program/Project	<input checked="" type="checkbox"/>	<input type="checkbox"/>	R. J. Cash		7-27-93	Communications	<input checked="" type="checkbox"/>	<input type="checkbox"/>	W. P. Whiting		5/4/93	RL Program/Project	<input checked="" type="checkbox"/>	<input type="checkbox"/>	R. F. Christensen		8-4-93	Publication Services	<input checked="" type="checkbox"/>	<input type="checkbox"/>	C. J. Forbes		8/9/93	Other Program/Project	<input type="checkbox"/>	<input checked="" type="checkbox"/>			
Review Required per WHC-CM-3-4	Yes	No	Reviewer - Signature	Indicates Approval	Date																																																																		
			<u>Name (printed)</u>	<u>Signature</u>																																																																			
Classification/Unclassified Controlled Nuclear Information	<input type="checkbox"/>	<input checked="" type="checkbox"/>																																																																					
Patent - General Counsel	<input checked="" type="checkbox"/>	<input type="checkbox"/>	S. W. Berglin		8/2/93																																																																		
Legal - General Counsel	<input checked="" type="checkbox"/>	<input type="checkbox"/>	S. W. Berglin																																																																				
Applied Technology/Export Controlled Information or International Program	<input type="checkbox"/>	<input checked="" type="checkbox"/>																																																																					
WHC Program/Project	<input checked="" type="checkbox"/>	<input type="checkbox"/>	R. J. Cash		7-27-93																																																																		
Communications	<input checked="" type="checkbox"/>	<input type="checkbox"/>	W. P. Whiting		5/4/93																																																																		
RL Program/Project	<input checked="" type="checkbox"/>	<input type="checkbox"/>	R. F. Christensen		8-4-93																																																																		
Publication Services	<input checked="" type="checkbox"/>	<input type="checkbox"/>	C. J. Forbes		8/9/93																																																																		
Other Program/Project	<input type="checkbox"/>	<input checked="" type="checkbox"/>																																																																					
Information conforms to all applicable requirements. The above information is certified to be correct.																																																																							
References Available to Intended Audience <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			INFORMATION RELEASE ADMINISTRATION APPROVAL STAMP Stamp is required before release. Release is contingent upon resolution of mandatory comments. <div style="text-align: center;">  MASTER </div>																																																																				
Transmit to DOE-HQ/Office of Scientific and Technical Information <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No																																																																							
Author/Requestor (Printed/Signature) <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No H. Babad 7/26/93																																																																							
Intended Audience <input type="checkbox"/> Internal <input type="checkbox"/> Sponsor <input checked="" type="checkbox"/> External																																																																							
Responsible Manager (Printed/Signature) <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No R. J. Cash 7/27/93			Date Cancelled																																																																				
			Date Disapproved																																																																				

The Role of Aging in Resolving the Ferrocyanide Safety Issue

H. Babad
J. E. Meacham
B. C. Simpson
R. J. Cash

Date Published
August 1993

Prepared for the U.S. Department of Energy
Office of Environmental Restoration and
Waste Management



Westinghouse
Hanford Company

P.O. Box 1970
Richland, Washington 99352

Hanford Operations and Engineering Contractor for the
U.S. Department of Energy under Contract DE-AC06-87RL10930

Approved for Public Release

**THE ROLE OF AGING IN RESOLVING
THE FERROCYANIDE SAFETY ISSUE**

**H. Babad
J. E. Meacham
B. C. Simpson
R. J. Cash**

ABSTRACT

A chemical process called aging, in which stored ferrocyanide waste could be dissolved and dispersed among waste tanks, or destroyed by radiolysis and hydrolysis, has been proposed at the Hanford Site. This paper summarizes the results of applied research, characterization, and modeling activities on Hanford Site ferrocyanide waste material that support the existence of a chemical aging mechanism. Test results from waste simulants and actual waste tank materials are presented and compared with theoretical estimates. Chemical and energetic behavior of the materials are the key indicators of destruction or dispersion. Screening experiments on vendor-prepared sodium nickel ferrocyanide and the initial results from core sampling support the concept that aging of ferrocyanide is taking place in the waste tanks at the Hanford Site. This report defines the concept of waste aging and explains the role that aging could play in resolving the Hanford Site ferrocyanide safety issue.

LIST OF TERMS

AA	Atomic Absorption
DSC	Differential Scanning Calorimetry
DST	Double-Shell Tank
EDS	Energy Dispersive Spectroscopy
ESEM	Environmental Scanning Electron Microscopy
FY	Fiscal Year
IC	Ion Chromatography
IR	Infrared
PNL	Pacific Northwest Laboratory
SST	Single-Shell Tank
TBP	Tributyl Phosphate
XRD	X-Ray Diffraction

CONTENTS

1.0 INTRODUCTION1-1

2.0 CONCEPT OF WASTE AGING2-1

3.0 INVESTIGATION OF AGING3-1

 3.1 FERROCYANIDE TANK HISTORY3-1

 3.2 FERROCYANIDE WASTE SIMULANTS3-3

 3.3 FERROCYANIDE TANKS 241-C-109 AND 241-C-112
 CHARACTERIZATION RESULTS3-4

 3.4 PACIFIC NORTHWEST LABORATORY AGING TESTS3-5

 3.5 PLANNED WORK3-11

4.0 FERROCYANIDE SAFETY ISSUE RESOLUTION STRATEGY4-1

5.0 CONCLUSION5-1

6.0 REFERENCES6-1

LIST OF FIGURES

3-1 Solubility of Vendor-Prepared $\text{Na}_2\text{NiFe}(\text{CN})_6$ in
NaOH as a Function of pH at 25 °C 3-8

3-2 Solubility of Vendor Material Sodium Ion (Na^+) Dependence, pH 13 3-10

4-1 Logic Determining In Situ Safe Storage of Ferrocyanide
Waste in Hanford Site Single-Shell Tanks. 4-2

LIST OF TABLES

3-1 Ferrocyanide Tank Waste Alkalinity 3-2

3-2 Heats of Reaction of Various Simulants 3-3

3-3 Comparison of Waste Material from Tanks 241-C-112
and 241-C-109 with Simulants 3-5

3-4 Conditions and Results for Preliminary Experiments 3-6

4-1 Information Sources Associated With Evaluation of Safety
Factors for Ferrocyanide Tanks 4-3

THE ROLE OF AGING IN RESOLVING THE FERROCYANIDE SAFETY ISSUE

1.0 INTRODUCTION

Public Law 101-510, Section 3137, requires development of plans to resolve safety issues associated with high-level waste tanks at the Hanford Site (PL101-510 1990). Of particular concern are events that could lead to excessive temperature changes or pressure increases resulting in a release of radioactive material. Fifty-four tanks have been identified and categorized by tank contents as potential safety concerns. These include tanks that (1) contain ferrocyanide compounds; (2) have the potential for flammable gas generation; (3) contain organics; or (4) have high-heat loads. The ferrocyanide and hydrogen gas safety issues have been declared unreviewed safety questions (DOE 1991) because postulated accident scenarios may fall outside safety envelopes as defined by existing safety analysis documentation.

Since the 1940s, radioactive waste from defense operations has been accumulating in underground high-level waste tanks at the Hanford Site. There are 177 of these waste tanks: 149 single-shell tanks (SSTs), and 28 double-shell tanks (DSTs). With the increased emphasis on defense materials production in the early 1950s, it became necessary to increase the available waste tank storage volume while minimizing construction of new tanks. A process was developed that allowed disposal of large volumes of low-activity liquids to cribs and trenches. The treatment involved scavenging ^{137}Cs and ^{90}Sr from uranium recovery plant waste using ferrocyanide and other chemicals in a carrier precipitation process. This action reduced the waste volume in the tanks by over 40 million gallons, and minimized the amount of long-lived radionuclides discharged to the ground.

Ferrocyanide is a complex of ferrous ion and cyanide that is considered nontoxic because it is stable in aqueous solutions. However, in the presence of oxidizing materials, such as nitrates/nitrites, near-stoichiometric amounts of ferrocyanide can be made to explode under special conditions in the laboratory by (1) heating it to high temperatures (above 285 °C); or (2) by an electrical spark of sufficient energy to heat the mixture. The explosive nature of ferrocyanide in the presence of an oxidizer has been known for decades, but the conditions under which the compound can undergo an uncontrolled exothermic reaction had not been thoroughly studied until recently. Because the scavenging process involved precipitating ferrocyanide from solutions containing nitrate and nitrite, it is likely that an intimate mixture of ferrocyanides with nitrates and nitrites exists in parts of some of the Hanford Site SSTs.

Known or suspected major constituents of the ferrocyanide waste include: sodium nitrate; sodium nitrite; metal silicates; alkali metal hydroxides; phosphates; sulfates; carbonates of iron; calcium and other metals; ferrocyanide and uranium salts; and fission products created by processing irradiated fuel. Alkaline aluminum cladding waste was later added to some of

the ferrocyanide tanks and may have become mixed with the ferrocyanide sludge. Based upon flowsheet data and process records, there are different types of ferrocyanide tank waste.

Three flowsheets were used to scavenge the radionuclides from aqueous waste. The T Plant flowsheet was used to treat first-cycle waste from the bismuth-phosphate process. This generated about 10 percent of the total ferrocyanide waste. The U Plant flowsheet treated acid solvent extraction waste after the uranium had been recovered from bismuth phosphate "metal waste" using the tributyl phosphate (TBP) process. The U Plant process produced about 70 percent of the total ferrocyanide waste. The In Farm flowsheet treated the basic "metal waste" previously treated by the TBP process but not scavenged for soluble radionuclide removal. This process produced the highest concentration of ferrocyanide sludge, and accounts for the remaining 20 percent of the total ferrocyanide waste.


The In Farm ferrocyanide waste originated by treating the supernatants of waste that had previously undergone uranium recovery (the TBP process). The waste had been neutralized and sent back to the tanks for settling before cesium and strontium scavenging. Consequently, the In Farm waste contained less inert solids in the waste stream and was more concentrated in ferrocyanide salts than waste treated using the T Plant and U Plant flowsheets.

This report focuses on processes that appear to occur during extended storage of ferrocyanide waste in Hanford Site tanks. It defines the concept of waste aging and focuses on the role that such processes could play in closing the ferrocyanide safety issue. The report summarizes the results of applied research, characterization, and modeling activities on ferrocyanide waste material. It also provides the results of theoretical estimates and studies on waste simulants and actual tank material that focus on the task of destroying some of the ferrocyanide inventory in Hanford Site waste tanks.


2.0 CONCEPT OF WASTE AGING

The aging of ferrocyanide waste is broadly defined in terms of those processes that result in a lower potential for ferrocyanide reactions. This includes dissolution and removal of ferrocyanide during liquid transfers, or degradation of the ferrocyanide to a less energetic form by hydrolysis and/or radiolysis. A detailed review of literature relating to ferrocyanide aging is scheduled to be released at the end of fiscal year (FY) 1993.



Insoluble sodium nickel ferrocyanide, the major component of the ferrocyanide sludges formed during the radioisotope scavenging campaign, will dissolve in a caustic solution containing 0.01 M hydroxide. This has been demonstrated using relatively pure vendor-prepared material in alkaline salt solutions (Lilga et al. 1992). The rate of dissolution increases with increasing hydroxide concentration (see Section 3.2). Dissolution of sodium nickel ferrocyanide results in soluble sodium ferrocyanide and a nickel hydroxide precipitate via equation 1.




Soluble ferrocyanide is a byproduct of many industries, including aluminum manufacturing, iron and steel making, metal finishing (Robuck and Luthy 1979), and chemical manufacturing. Because ferrocyanide wastes are not uncommon, several papers have been written on alkaline hydrolysis reactions involving ferrocyanide. Research (Robuck and Luthy 1979) using spent potlining leachate has demonstrated that ferrocyanide will hydrolyze to form formate, ferric oxide, and ammonia (see equation 2). Similar reactions should be possible in the alkaline conditions found in the ferrocyanide SSTs. The reaction was found to be first order with respect to cyanide, and zero-order with respect to hydroxide for pH values greater than 10 (Robuck and Luthy 1979).



The literature (Wiegand and Tremelling 1972) suggests that hydrolysis is actually a two-step process. The ferrocyanide dissociates to free cyanide, which is then hydrolyzed to form formate and ammonia (see equations 3 and 4 [Wiegand and Tremelling 1972]). The hydrolysis reaction is very temperature dependent. The reaction proceeds slowly at room temperature, with a three-fold increase in reaction rate for every 10 °C rise in temperature.



The effect of γ -radiation on ferrocyanide solutions has been investigated, but offers very complex chemistry. The decomposition of water by ionizing radiation yields radical and molecular products (see equation 5). In turn, these products can react to reduce or oxidize ferric or ferrous iron in solution. It has been demonstrated that, whereas ferrocyanide is oxidized in aerated acid solution, ferricyanide is reduced at pH greater than 11 (Hughes and Willis 1961). However, no mechanism was put forward to account for these observations.



Recent experiments at Pacific Northwest Laboratory (PNL) suggest that soluble ferrocyanide salts produce cyanide ions by radiolysis (Lilga et al. 1992). This may lead to an increase in the rate of hydrolysis; however, it is unknown whether radiolysis plays an important factor in aging of Hanford Site ferrocyanide waste. Little is known about the effect of γ -radiation on insoluble complex ferrocyanide salts, although degradation by ultraviolet radiation has been observed in ferrocyanide compounds (Ohno and Tsuchihashi 1965; MacDiarmid and Hall 1953; Masri and Haissinsky 1963).

To validate the aging concept, two events must be evident. First, the postulated mechanisms must be demonstrated on flowsheet waste simulants and eventually on real ferrocyanide waste. Second, a means of delivering the alkali to the ferrocyanide-precipitated waste must be shown. Experimental data must confirm that initially insoluble ferrocyanide salts will dissolve and/or degrade under conditions known to have existed in the ferrocyanide tanks.

The slow diffusion of materials in aqueous heterogeneous waste systems is known to occur; however, the time required for such diffusion is long. Questions remain whether a diffusion-controlled process could dissolve waste near the bottom of the tank. Modeling and perhaps some experimental studies are needed to determine the time required for diffusion of alkali through the deepest bed of settled waste.

Mechanisms for accelerated mixing in the tanks have been postulated. Three tank circumstances are worth noting: (1) some solutions added to the ferrocyanide tanks were of higher specific gravity than the solutions produced during cesium precipitation -- resulting in a higher density liquid covering a lower density liquid; (2) vertical temperature profiles have revealed temperature gradients between the waste surface and the tank bottom; and (3) radiolysis of water results in the formation of hydrogen gas. Differences in liquid densities, temperature gradients, and the upward migration of gas bubbles through the sludge could all contribute to microconvective mixing in the ferrocyanide waste tanks. The possibility that such a microconvection phenomenon might exist is supported by discussions with Professors Pigford and Chamber at the University of California, Berkeley, who are international authorities on diffusion and mixing phenomena in porous media.

3.0 INVESTIGATION OF AGING

3.1 FERROCYANIDE TANK HISTORY

Although the precipitation of sodium nickel ferrocyanide was done at slightly alkaline conditions (pH = 8.5 - 10), historical data indicate that the ferrocyanide tanks were used for a variety of waste management operations that exposed the tanks to alkaline waste. Highly alkaline reprocessing waste from the caustic dissolution of aluminum cladding and/or highly alkaline evaporator bottoms from waste concentration operations were added to many of the ferrocyanide tanks (Anderson 1990).

In 1992, an analysis of the SSTs was made to assess possible impacts of low pH on a variety of potential tank reactivity hazards. An excerpt from the alkalinity data obtained during this effort is presented in Table 3-1 (for complete details, refer to Table B-2 in WHC-EP-0347, Supplement [Ryan et al. 1992]). Historic data for the ferrocyanide tanks suggest that most of the tanks are alkaline, with a hydroxide concentration greater than 0.1 M.

Values for pH presented in Table 3-1 contain considerable error. Ionic strength in the supernatant and drainable liquid samples exceeded 4.0 N, making a direct correlation between hydrogen ion activity and concentration meaningless. Therefore, the pH data are presented as a relative measure of acidity among the high ionic liquid samples. The hydroxide concentration measurements presented are a more reliable measure of alkalinity. Hydroxide concentrations were measured by direct potentiometric titration of the solutions with a standardized acid.

Depending on the waste tank, large volumes of various waste types were transferred in and out of the tank during its active life. To prevent leaks, there has been an ongoing stabilization program of saltwell pumping in the SSTs to transfer drainable liquid to the DSTs. This may have dispersed ferrocyanide among several tanks. A total of 106 SSTs have been stabilized, including 17 of the 24 ferrocyanide tanks.

Another important parameter in the aging process is temperature. Higher temperatures lead to faster dissolution and hydrolysis. The current bulk temperature of the ferrocyanide tanks ranges between approximately 20 to 55 °C. Temperatures in the tanks have dropped steadily since the scavenging campaign ended, and the highest current temperature is in tank 241-BY-104 (approximately 55 °C). However, temperatures have historically been much higher. Temperature data from 1961 to 1964 show C Farm ferrocyanide tanks with temperatures ranging between 66 and 82 °C (Mercier et al. 1981). Temperatures in BY Farm tanks have been even higher, ranging between 66 and 93 °C from 1974 to 1980 (Grigsby et al. 1991).

Table 3-1. Ferrocyanide Tank Waste Alkalinity*.

	pH	OH, M	Sample Date	Notes
BY-105	13.3	0.78	11/90	Supernatant
BY-111	9.6	NA ¹	6/56 ²	
C-108	11.8	0.48	9/75	Supernatant
C-109	13.7	0.5	11/90	Supernatant
C-112	12.1	0.67	11/74	
	11.9	0.49	6/75	
	9.0 - 10.5	NA	3/92	Water leach of core segments ³
T-101	13.0	0.27	3/75	Supernatant
	13.3	0.21	9/89	
T-107	13.2	0.16	3/65	Supernatant
	12.3	0.08	9/75	
	11.1	0.025	9/89	
TY-101	12.7	0.05	12/82	
	10.0	NA	9/85	Water leach of core composite
TY-103	12.0	0.24	3/65	Supernatant
	11.7	NA	2/72	
	9.5 - 12.2	0 - 0.017	9/85	Drainable liquid
TY-104	12.0	0.32	3/65	
	12.1	NA	2/72	
	12.1 - 12.2	0.013 - 0.016	8/85	Drainable liquid

¹NA = Not available.

²A more recent sample has not been found.

³Water leach of 1 g of core sample with 100 g of water.

*Ryan et al. 1992

3.2 FERROCYANIDE WASTE SIMULANTS

Simulated ferrocyanide sludge, representative of that formed during the scavenging campaign, was prepared using original flowsheets (U Plant, In Farm, and T Plant). No radioactive isotopes were used in the simulant preparation; however, nonradioactive cesium was added to the In Farm simulant. The U Plant flowsheets represent 70 percent of the ferrocyanide that was used at the Hanford Site and found in 17 of the 24 Ferrocyanide Watch List tanks. The In Farm flowsheet waste was placed into 4 tanks and accounts for 20 percent of the total ferrocyanide added.

The third scavenging campaign employed used was the T Plant flowsheet, which accounts for 10 percent of the ferrocyanide that was added to the waste tanks. This waste was put into 4 tanks, including one tank (241-TK-118) that also received U Plant flowsheet waste. Tests using this simulant are scheduled during the last half of FY 1993.

Tests were conducted on U Plant and In Farm simulant dried under vacuum at 60 °C for 24 hours. U Plant simulant did not exhibit explosive reactions even when heated to 500 °C. Adiabatic calorimetry tests revealed that dry U Plant simulant will self heat from 270 to 620 °C. The In Farm simulant exhibited slow propagating reactions (5 to 10 cm/min) when externally heated to 245 °C. This is equivalent to a burn, and is much slower than a detonation (> 300 m/s). A summary of the heat of reaction recorded during adiabatic calorimetry tests is presented in Table 3-2.

Table 3-2. Heats of Reaction of Various Simulants*.

Material	Heat of reaction ¹
$\text{Na}_2\text{NiFe}(\text{CN})_6$	-945 cal/g of dry material
U Plant 2 Simulant	-84 cal/g of dry material
In Farm 1 Simulant	-250 cal/g of dry material

¹Values on a dry basis with all free water removed. Samples still contained approximately 2 to 3 wt% chemically bound water.

*Fauske 1992

The highest fuel (as sodium nickel ferrocyanide) content in the simulants was determined to be less than 26 wt% on a dry basis. Propagation experiments on the simulants showed that greater than 13 wt% fuel and less than 12 wt% moisture was required to sustain a propagating reaction (Fauske 1992).

The concentration limit for ferrocyanide propagating reactions in actual waste must still be established by laboratory investigations. Tank waste analyses can then be used to demonstrate that this concentration is not exceeded within the waste. Sampling and subsequent analysis, combined with modeling, should provide the technical basis for removing tanks from the Ferrocyanide Watch List. If this is not possible, then moisture and/or temperature control may be required to ensure in situ safe storage.

3.3 FERROCYANIDE TANKS 241-C-109 AND 241-C-112 CHARACTERIZATION RESULTS

Core samples obtained from ferrocyanide tanks 241-C-109 and 241-C-112 have been analyzed. These tanks received wastes from the In Farm flowsheet and should contain the highest concentration of ferrocyanide. Analyses were performed on quarter segments (12.1 cm [4.75 in.] slices) so that the effect of layering could be evaluated. A brief comparison between characteristics of quarter segment samples extruded from tank 241-C-112 and simulant material is presented in Table 3-3. With the noted exception of total cyanide and energetics, there was good agreement between simulant sludge properties and those observed for actual waste material (Cash et al. 1993; Jeppson and Wong 1993; Simpson et al. 1993).

Preliminary analytical results from core samples of tank 241-C-109 have also shown low energetics. Only one core segment exhibited any exothermic activity, and the rest of the samples contained a moderate to large endotherm in the temperature range where a ferrocyanide exothermic peak was expected. Tank 241-C-109 material appears to be no more reactive than tank 241-C-112 waste.

Low total cyanide and energetic values are significant. Core sampling offers the best evidence to date that degradation has occurred in the ferrocyanide tanks. Total cyanide and energetic values are approximately an order of magnitude lower than predicted by ferrocyanide sludge simulants and flowsheet mass balances. Aging offers an explanation for these findings.

In addition to low energetics and cyanide values, there is more evidence of cyanide hydrolysis. Ammonia is a byproduct of cyanide hydrolysis (see equations 2 and 4). Gas analyses of tank dome spaces have discovered detectable concentrations (> 5 ppm) of ammonia in six of the eight ferrocyanide tanks tested. Ammonia concentrations have ranged from 20 to 255 ppm.

Table 3-3. Comparison of Waste Material from Tanks 241-C-112 and 241-C-109 with Simulants.

Analyte	In Farm Simulant	C-112 Core 34 ¼ Segment	C-112 Core 36 ¼ Segment	C-109 Core 47 ¼ Segment	C-109 Core 48 ¼ Segment	C-109 Core 49 ¼ Segment
Total Cyanide (wt%) ¹	15.7	0.43 to 0.97	0.40 to 0.92	0.30 to 0.55	0.87 to 1.1	0.35 to 0.81
ΔH (cal/g) ¹	-250	-28 to -38	-5 to -11	No Exotherm	-6.2 to -6.7	No Exotherm
Water (wt%)	41 to 50	45 to 58	41 to 64	18 to 39	21 to 40	21 to 40
Density (g/ml) ¹	1.5	1.5 to 1.6	1.3 to 1.6	NA ²	NA	NA

¹Values on a dry basis with all free water removed. Samples still contained approximately 2 to 3 wt% chemically bound water.

²NA = Not Available.

3.4 PACIFIC NORTHWEST LABORATORY AGING TESTS

Current studies seek to identify aging mechanisms that are taking place in the Hanford Site tanks as a result of exposure to highly alkaline aluminum decladding waste (from the reprocessing of aluminum-clad fuels in the plutonium-uranium extraction process) and highly alkaline evaporator bottoms from concentration of reprocessing waste. Aging processes may have dissolved, diluted, and slowly destroyed the ferrocyanide over the last 35 years. PNL studies are investigating the effects of pH, sodium-ion concentration, gamma radiation, and various anions on solubilization of vendor-prepared sodium nickel ferrocyanide (Lilga et al. 1992; Lilga and Schiefelbein 1993).

In the initial dissolution screening experiments, 1 g of vendor-prepared sodium nickel ferrocyanide was stirred and refluxed for 96 hours in 0.1 M and 1.0 M NaOH. These experiments were performed in standard laboratory glassware. Table 3-4 summarizes the conditions and results of the two experiments. The data indicate that vendor-prepared material dissolves in high-pH solutions to give insoluble nickel hydroxide and soluble ferrocyanide.

Table 3-4. Conditions and Results for Preliminary Experiments*

Caustic concentration	0.1 M NaOH	1.0 M NaOH
Initial pH	12.9	13.8
Final pH	10.5	13.0
$\text{Na}_2\text{NiFe}(\text{CN})_6 \cdot \text{Na}_2\text{SO}_4 \cdot 4.5 \text{H}_2\text{O}$ (g)	1.0005	1.0041
Moles $\text{Fe}(\text{CN})_6^{4-}$ or Ni^{+2}	1.85×10^{-3}	1.86×10^{-3}
Weight of recovered solids (g)	0.3316	0.5113
Solution [Fe] (mg/L)	2030	1600
Moles Fe in solution	1.82×10^{-3}	1.43×10^{-3}
Fraction total Fe in solution	98%	77%
Solution [Ni] (Mg/L)	39	3.3
Moles Ni in solution	3.32×10^{-5}	2.81×10^{-6}
Fraction total Ni in solution	1.8%	0.15%
$[\text{NH}_3]$ in gas (ppm)	30	375
Approximate moles NH_3 produced	8.04×10^{-8}	2.34×10^{-6}
Approximate %-yield NH_3	0.007	0.02

Atomic absorption (AA) analysis of the reaction supernatants revealed that essentially all of the iron was solubilized after 96 hours at reflux conditions. Very little of the nickel was found in the supernatant solutions. Environmental scanning electron microscopy (ESEM) and energy dispersive spectroscopy (EDS) of the soluble solids crystallized from the supernatant are consistent with the AA results, showing the presence of iron but not nickel. Infrared (IR) spectroscopy and x-ray diffraction (XRD) indicated that ferrocyanide ($\text{Fe}(\text{CN})_6^{4-}$) is the primary cyanide compound in solution.

Analysis using IR spectroscopy, ESEM, EDS, XRD, and Maussbauer spectroscopy were made to characterize the insoluble solids. ESEM analysis revealed the presence of nickel in the reaction precipitate. Iron was also detected at very low levels. Analysis by IR spectroscopy and XRD showed that the nickel-containing insoluble species is nickel hydroxide. In addition, IR spectroscopy and EDS showed the presence of significant quantities of silica, from etching the glassware used in these experiments. The larger weight of the insoluble solids obtained using 1.0 M NaOH is because of a larger amount of silica

*Lilga et al. 1992

etched from the glassware in this sample. For this reason, Teflon* labware was used in subsequent experiments. The Maussbauer spectrum of the insoluble solids from the 1.0 M NaOH dissolution is weak, indicating a low iron content.

In both experiments the presence of ammonia was detected. This indicates indicative of cyanide hydrolysis reactions. A greater degree of hydrolysis occurred in the more basic solution. The extent of hydrolysis was very low. After 96 hours the largest yield of ammonia was 0.02 percent (0.02 percent of the CN⁻ groups were converted to NH₃).

A more detailed study was conducted to determine the influence of pH, ionic strength, and the presence of tank waste simulant salts on the rate and extent of dissolution of the vendor-prepared sodium nickel ferrocyanide material. The primary difference between these experiments and the preliminary screening experiments is that they were performed at room temperature in Teflon labware.


A parametric experiment to study the effect of initial pH on ferrocyanide dissolution was conducted at starting pH values of 12, 13, and 14 (0.01 M, 0.1 M, and 1.0 M NaOH, respectively). Solutions were periodically sampled during the reaction and were analyzed for iron by AA (see Figure 3-1). At the end of the experiment, the final pH was measured and the soluble and insoluble solids were analyzed by IR spectroscopy, ESEM, EDS, XRD, and occasionally by Maussbauer spectroscopy. In some cases, the supernatant was analyzed for free cyanide, ferrocyanide, and ferricyanide by ion chromatography (IC).

Figure 3-1 shows that dissolution is 95 percent complete after 0.5 hour of stirring in 1 M NaOH (pH 14) at room temperature. The reaction at pH 12 is base-limited, but the base is rapidly consumed within 0.1 hour. At pH 13, a slight excess amount of base is present and the dissolution proceeds rapidly, at first, but then slows to reach about 85 percent completion in 144 hours. The dissolution would probably continue to completion at longer reaction times at pH 13.

Experiments were performed to determine the effect of solution ionic strength on the dissolution of ferrocyanide. For experiments conducted at the same initial pH, the rate and extent of dissolution tends to be lower at a higher sodium concentration. This was probably caused by a common ion effect in the high sodium-ion medium.

*Teflon is a trademark of the E. I. duPont de Nemours Company.

Figure 3-1. Solubility of Vendor-Prepared $\text{Na}_2\text{NiFe}(\text{CN})_6$ in NaOH as a Function of pH at 25 °C.




The influence of anions present in the ferrocyanide SSTs was also investigated (see Figure 3-2). Vendor-prepared sodium nickel ferrocyanide was dissolved in a saline solution of tank simulant salts to yield a solution with 1.0 M sodium concentration and a pH of 12.8, which was adjusted to pH 13. The results from these experiments showed that ferrocyanide dissolved faster in the pH 13 simulant salt solution than other pH 13 solutions tested. Adding sodium sulfate suppressed dissolution, while adding tank salts enhanced dissolution. The enhanced rate of dissolution with SST simulant salts is thought to be from buffering of the solution by phosphate.

Because the SST contents are not being mechanically mixed, an experiment investigating the dissolution of the vendor-prepared sodium nickel ferrocyanide in the presence of SST simulant salts was conducted under static conditions. The experiment was conducted in Teflon labware at pH 13 with simulant salts added to give 1 M sodium ion concentration. To minimize disturbance, the solution was sampled less frequently (24-hour intervals) than the stirred solutions. Prior to each sampling, a 5-second stirring was required to ensure a homogeneous solution phase. As expected, the rate of dissolution is slower in the static solution. Nevertheless, appreciable dissolution occurred. Approximately 40 percent was dissolved after 24 hours with no stirring, and 90 percent was dissolved after 6 days. IC analysis for free cyanide ion showed 9.1 ppm after 72 hours and 11.8 ppm after 144 hours.

Dissolution experiments have shown that the ferrocyanide-cesium compounds are quite insoluble in caustic solutions. Dicesium nickel ferrocyanide and In Farm ferrocyanide simulant were leached for 144 hours at room temperature in solutions containing 0.1 M to 4.0 M NaOH. AA analysis of the supernatants revealed no soluble cesium. Analyses of the remaining solids confirmed that all of the cesium was still present. Sodium nickel ferrocyanide was solubilized from the In Farm simulant material, but not cesium.

Gamma radiation experiments suggest that gamma radiation does not greatly affect the dissolution reaction. There was no increase in dissolution rate in the gamma pit experiments and similar rates were observed for unstirred irradiated and control solutions. A more complex mixture of iron cyanides in the insoluble fraction was found for the gamma radiated samples. This suggests that an iron cyanide species re-precipitates from solution. Further work is needed to determine if this is indeed the case and to identify the species of the iron cyanide re-precipitate.

Figure 3-2. Solubility of Vendor Material Sodium Ion (Na^+) Dependence, pH 13.



3.5 PLANNED WORK

The goal of the aging studies is to clarify the present condition of ferrocyanide sludge in Hanford Site SSTs. Understanding aging pathways will help interpret analytical results from supernatant, core, and vapor sampling. Knowing reaction rates and kinetic data under various temperature, concentration, and pH regimes should produce an approach for estimating current ferrocyanide concentration.

Preliminary dissolution, hydrolysis, and radiolysis experiments will be performed in FY 1993. A modeling effort to determine if microconvective mixing might have accelerated contact between ferrocyanide sludge and highly alkaline solutions added later to the SSTs is also being performed in FY 1993. The intent of these tasks is to (1) determine whether aging is possible; and (2) validate the chemical equations found in the literature under conditions simulating those which have existed in the ferrocyanide SSTs. Experiments completed in FY 1993 will be used to define the scope of experiments continued into FY 1994.

Experiments are investigating the effect of temperature, ionic strength, gamma radiation, and alkalinity on the dissolution, hydrolysis, and degradation of vendor-prepared sodium nickel ferrocyanide and the ferrocyanide flowsheet simulants. Studies in FY 1994 will attempt to define reaction rates and the chemical kinetics associated with dissolution and hydrolysis. A detailed test plan describing the work planned has been published as a PNL document (Lilga and Schiefelbein 1993).

This page intentionally left blank.

4.0 FERROCYANIDE SAFETY ISSUE RESOLUTION STRATEGY


To put the role of aging into perspective, the logic that is being used by the Ferrocyanide Safety Program for resolution of the ferrocyanide safety issue is discussed in this section. To ensure safe storage of the ferrocyanide waste until final disposal is completed, the waste must remain in a non-reactive form. Three alternative conditions can bound safe storage in any given ferrocyanide tank. They relate to (1) the presence of a dangerous amount of fuel inventory in the oxidizer-rich waste; (2) potentially dangerous concentrations of fuel and oxidizer, or the ability to control tank conditions to prevent a dangerous reaction from initiating. To resolve the safety issue, it must be demonstrated on a tank-by-tank basis (or on a group of tanks) that the tank contents are either:

- Intrinsically safe--The tank contains an insignificant (low) fuel inventory
- Passively safe--The tank contains a low fuel concentration
- In a state of controlled safety--The fuel concentration is sufficient for a reaction if the waste is dry and a high temperature is present, but temperature and moisture control are guaranteed (having an effective monitoring and corrective system in place). In addition, controlled safety requires that the controlled conditions can be maintained over the long term for all tank farm operations.

If the above criteria cannot be met, the tank's contents may be subject to mitigation or at least fall into a category of tanks for a candidate for early retrieval and remediation. A diagram of the in situ safe storage logic is presented in Figure 4-1.

The factors affecting the judgment of safety for the ferrocyanide-containing tanks (inventory, concentration, and/or control limits) are presented in Table 4-1. No single source of data is likely to provide sufficient proof of safety for any given tank other than those tanks that either received an insignificant inventory of fuel or were emptied of the suspect materials. Rather, a case must be established and documented showing where the preponderance of data and analyses clearly suggest that continued storage of the waste is safe under specified operating safety requirements.

Figure 4-1. Logic Determining In Situ Safe Storage of Ferrocyanide Waste in Hanford Site Single-Shell Tanks.



29305087.1

Table 4-1. Information Sources Associated With Evaluation of Safety Factors for Ferrocyanide Tanks.

SAFETY FACTOR	DATA SOURCE	INFORMATION NEED ¹
INVENTORY LIMIT	<ul style="list-style-type: none"> • HISTORICAL INFORMATION • WASTE CHARACTERIZATION DATA • MODELING • SIMULATED WASTE STUDIES 	<ul style="list-style-type: none"> • INVENTORY ESTIMATES FROM TRANSFER RECORDS • FLOWSHEET INVENTORY PROJECTIONS • CHEMICAL AND PHYSICAL PROPERTIES FROM TANK SAMPLES • TRANSIENT AND MAXIMUM TEMPERATURE ESTIMATES OF FERROCYNIDE CONTAINING TANKS UNDER NORMAL AND "HOT SPOT" CONDITIONS • THERMODYNAMIC ENERGY ESTIMATES • ACTUAL ENERGY DENSITY MEASUREMENTS OF FLOWSHEET SIMULANTS • DEGRADATION OR DECOMPOSITION (AGING STUDIES)
CONCENTRATION LIMITS	<ul style="list-style-type: none"> • HISTORICAL INFORMATION • WASTE CHARACTERIZATION DATA • MODELING • SIMULATED WASTE STUDIES 	<ul style="list-style-type: none"> • FLOWSHEET ANALYSIS • CONCENTRATION FACTORS • MULTIPLE POINT WASTE MEASUREMENTS TO DEFINE WASTE CONCENTRATION PROFILES • LIQUID AND SOLID SAMPLE ANALYSES • MOISTURE MEASUREMENTS • THERMODYNAMIC ENERGY ESTIMATES • THERMAL MODELING OF TANK RESPONSES • ESTIMATES OF TANK FLUID MIXING (e.g., MICROCONVECTION) • SIMULATED WASTE STUDIES <ul style="list-style-type: none"> - FUEL DISPERSION MECHANISM - DEGRADATION PATHWAYS - FUEL CONCENTRATION PATHWAYS - INITIATORS AND CATALYSTS
CONTROL LIMITS	<ul style="list-style-type: none"> • HISTORICAL INFORMATION • WASTE CHARACTERIZATION DATA • MONITORING DATA • ENERGETICS AND REACTION DYNAMICS 	<ul style="list-style-type: none"> • ANALYSIS OF TANK RECORDS • WASTE SURFACE SAMPLE ANALYSIS (SURFACE MOISTURE AND TEMPERATURE) • CONCENTRATIONS OF KEY CONSTITUENTS • ENHANCED TANK MOISTURE MONITORING DATA • ENHANCED TEMPERATURE MONITORING DATA • THERMODYNAMIC ENERGY ESTIMATES • THERMAL AND STRUCTURAL MODELING OF THE TANKS

¹The data needs defined are not mutually exclusive. For example, characterization-based data may serve to prove that a tank contains a low inventory of ferrocyanide or that the concentration of ferrocyanide is low.

This page intentionally left blank.

5.0 CONCLUSION

Ferrocyanide-containing SSTs at the Hanford Site have been exposed to highly alkaline solutions. Experiments with ferrocyanide sludge simulants and vendor-prepared sodium nickel ferrocyanide have demonstrated that ferrocyanide will dissolve in caustic solution. Soluble ferrocyanide could have diffused or been convected into the bulk of the waste and subsequently diluted during waste transfer operations. Chemical and radiolytic aging may have converted the ferrocyanide to lower energy reaction products. Transferring soluble ferrocyanide to highly alkaline DSTs, as part of the Hanford Site stabilization program, would enhance chemical decomposition by bypassing a need for a diffusion or microconvection mechanism within the current ferrocyanide tanks.

Data on vendor-prepared sodium nickel ferrocyanide and results from core sampling of tanks 241-C-109 and 241-C-112 support the supposition that aging of ferrocyanide has occurred in the tanks during their 35-year storage period. However, while all conclusions supporting aging are encouraging, they are also tentative. Key portions of the ferrocyanide research program, when completed, will clarify the aging mechanisms.

This page intentionally left blank.

6.0 REFERENCES

- Anderson, J. D., 1990, *A History of the 200 Area Tank Farms*, WHC-MR-0132, Westinghouse Hanford Company, Richland, Washington.
- Cash, R. J., B. C. Simpson, and H. Babad, 1993, *Recent Results from Characterization of Ferrocyanide Wastes at the Hanford Site*, WHC-SA-1701-FP, Westinghouse Hanford Company, Richland, Washington.
- DOE, 1991, *Unreviewed Safety Questions*, DOE Order 5480.21, U.S. Department of Energy, Washington, D.C.
- Fauske, H. K., 1992, *Adiabatic Calorimetry and Reaction Propagation Rate Tests with Synthetic Ferrocyanide Materials Including U-Plant 1, U-Plant 2, In-Farm 1, In-Farm 2 and Vendor Procured Sodium Nickel Ferrocyanide*, WHC-SD-WM-RPT-054, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Grigsby, J. M., D. B. Bechtold, G. L. Borsheim, M. D. Crippen, D. R. Dickinson, G. L. Fox, D. W. Jeppson, M. Kummerer, J. M. McLaren, J. D. McCormack, A. Padilla, B. C. Simpson, and D. D. Stepnewski, 1991, *Ferrocyanide Waste Tank Hazard Assessment - Interim Report*, WHC-SD-WM-RPT-032, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Hughes, G., and C. Willis, 1961, *The Radiolysis of Ferro- and Ferri-cyanide Solutions*, Department of Inorganic, Physical and Industrial Chemistry, Liverpool University, Great Britain.
- Jeppson, D. W. and J. J. Wong, 1993, *Ferrocyanide Waste Simulant Characterization*, WHC-EP-0631, Westinghouse Hanford Company, Richland, Washington.
- Lilga, M. A., M. R. Lumetta, W. F. Riemath, R. A. Romine, and G. F. Schiefelbein, 1992, *Ferrocyanide Safety Project, Subtask 3.4, Aging Studies FY 1992 Annual Report*, PNL-8387, Pacific Northwest Laboratory, Richland, Washington.
- Lilga, M. A. and G. F. Schiefelbein, 1993, *FY 1993 Ferrocyanide Tank Safety Project: Effects of Aging on Ferrocyanide Wastes Test Plan for the Remainder of FY 1993*, PNL-SA-22687, Pacific Northwest Laboratory, Richland, Washington.
- MacDiarmid, A. G., and N. F. Hall, 1953, "Illumination-pH Effects in Solutions of Complex Cyanides," *J. Am. Chem Soc.*, vol. 75, pp. 5204-7.
- Masri, E., and M. Haissinsky, 1963, "Radiolytic Transformations. Gamma-Radiolysis of Potassium Ferro- and Ferricyanide Solutions," *Chem. Phys.*, vol. 60, pp. 397-401.

- Mercier, P. F., M. D. Wonacott, and C. DeFig-Price, 1981, *Survey of the Single-Shell Tank Thermal Histories*, RHO-CD-1172, Rockwell Hanford Operations, Richland, Washington.
- Ohno, S., and E. Tsuchihasi, 1965, "The Photochemistry of Hexacyanoferrate(II) Ions in Aqueous Solutions," *Bull. Chem. Soc.*, vol 38, Japan, pp. 1052-3.
- Public Law 101-510, 1990, "Safety Measures for Waste Tanks at Hanford Nuclear Reservation," Section 3137 of *National Defense Authorization Act for Fiscal Year 1991*.
- Robuck, S. J., and R. G. Luthy, 1989, "Destruction of Iron-Complexed Cyanide by Alkaline Hydrolysis," *Wat. Sci. Tech.*, vol. 21, Brighton, Great Britain, pp. 547-58.
- Ryan, J. L., D. D. Wodrich, G. S. Barney, G. L. Borsheim, D. L. Becker, W. C. Calos, M. J. Klem, R. E. Van der Cook, 1992, *Summary of Single-Shell Tank Waste Stability*, WHC-EP-0347 Supplement, Westinghouse Hanford Company, Richland, Washington.
- Simpson, B. C., G. L. Borsheim, and L. Jensen, 1993, *Tank Characterization Data Report: Tank 241-C-112*, WHC-EP-0640, Westinghouse Hanford Company, Richland, Washington.
- Wiegand, G. H., and M. Tremelling, 1972, "The Kinetics and Mechanisms of the Decomposition of Potassium Cyanide in Aqueous Alkaline Medium, Hydrolysis of the Simplest Nitrile, HCN," *J. Organic Chem.*, vol. 37, pp. 914-16.

DISTRIBUTION

Number of copies

OFFSITE

12	<u>U.S. Department of Energy</u> EM-35, Trevion II Washington, D.C. 20585 John C. Tseng
1	<u>U.S. Department of Energy</u> Savannah River Operations Office P.O. Box A Aiken, South Carolina 29808 Thomas C. Temple
1	Charles S. Abrams 1987 Virginia Idaho Falls, ID 83404
1	David O. Campbell 102 Windham Road Oak Ridge, TN 37830
1	Fred N. Carlson 6965 North 5th West Idaho Falls, ID 83401
1	Donald T. Oakley 409 12th Street SW, Suite 310 Washington, DC 20024-2188
1	Arlin K. Postma 3640 Ballard Road Dallis, Oregon 97338
1	William R. Prindle 1556 Crestline Drive Santa Barbara, CA 93105

DISTRIBUTION (cont)

Number of copies

OFFSITE

1 **Alfred Schneider**
5005 Hidden Branches Drive
Dunwoody, GA 30338

1 **Air Products & Chemicals, Inc.**
7201 Hamilton Blvd
Allentown, PA 18195-1501

George E. Schmauch

1 **Battelle Columbus Laboratories**
505 King Avenue
Columbus, OH 43201-2693

James A. Gieseke

2 **Brookhaven National Laboratory**
Upton, NY 11973

Kamal K. Bandyopadhyay
Morris Reich

1 **Design Science, Inc.**
163 Witherow Road
Sewickley, PA 15143

Gary Powers

1 **Fauske and Associates, Inc.**
16W070 W. 83rd St.
Burr Ridge, IL 60521

Hans K. Fauske

DISTRIBUTION (cont)

Number of copies

OFFSITE

1	<u>Florida State University</u> Department of Chemistry B-164 Tallahassee, FL 32306 Greg R. Choppin
1	<u>Harvard University</u> 295 Upland Avenue Newton Highlands, MA 02161 Melvin W. First
1	<u>Hazards Research Corporation</u> 200 Valley Road, Suite 301 Mt. Arlington, NJ 07856 Chester Grelecki
1	<u>Lawrence Livermore National Laboratory</u> P.O. Box 808, L-221 Livermore, CA 94550 Billy C. Hudson
4	<u>Los Alamos National Laboratory</u> P.O. Box 1663 Los Alamos, NM 87545 Steve F. Agnew Steve W. Eisenhower Thomas E. Larson L. Harold Sullivan

DISTRIBUTION (cont)

Number of copies

OFFSITE

1 MIT/Department of Nuclear Engineering
77 Massachusetts Ave.
Room 24-102
Cambridge, MA 02139

Mujid S. Kazimi

1 Nuclear Consulting Services, Inc.
P.O. Box 29151
Columbus, OH 43229

J. Louis Kovach

Oak Ridge National Laboratory

1 Emory D. Collins
P.O. Box 2008
7930, MS-6385
Oak Ridge, TN 37831-6385

1 Charles W. Forsberg
P.O. Box 2008
MS-6495
Oak Ridge, TN 37831-6495

1 Thomas S. Kress
P.O. Box 2009
9108, MS-8088
Oak Ridge, TN 37831-8088

1 Rice University
5211 Paisley
Houston, TX 77096

Andrew S. Veletsos

DISTRIBUTION (cont)

Number of copies

OFFSITE

- 1 Sandia National Laboratory
P.O. Box 5800
Albuquerque, NM 87185
- Scott E. Slezak
- 4 Science Applications International Corporation
12850 Middlebrook Road
Trevion I, Suite 300
Germantown, MD 20874
- Ray S. Daniels (3)
John M. Saveland
- 1 University of South Carolina
Department of Electrical and Computer Engineering
Swearingen Engineering Center
Columbia, SC 29208
- Joseph S. Byrd
- 1 University of Washington
Center for Process Analytical Chemistry
Chemistry Department BG-10
Seattle, WA 98195
- Bruce R. Kowalski
- 1 Vanderbilt University
P.O. Box 1596, Station B
Nashville, TN 37235
- Frank L. Parker

DISTRIBUTION (cont)
Number of copiesONSITE

11	<u>U.S. Department of Energy, Richland Field Office</u>	
	R. F. Christensen (6)	A4-02
	R. E. Gerton	A4-02
	A. G. Krasopoulos	A5-55
	Public Reading Room	A1-65
	RL Docket File (2)	A3-11
9	<u>Pacific Northwest Laboratory</u>	
	R. T. Allemann	K7-15
	S. A. Bryan	P7-25
	B. M. Johnson	K1-78
	M. A. Lilga	P8-38
	R. D. Scheele	P7-25
	G. F. Schiefelbein	P8-38
	D. M. Strachan	K2-38
	PNL Technical Files	K1-11
	Hanford Technical Library	P8-55
63	<u>Westinghouse Hanford Company</u>	
	H. Babad (12)	R2-08
	D. B. Bechtold	T6-50
	D. C. Board	S1-57
	G. L. Borsheim	R2-11
	V. C. Boyles	R1-49
	S. L. Bradley	B3-06
	R. J. Cash (2)	R2-32
	M. D. Crippen	L5-31
	G. M. Christensen	H4-21
	R. D. Crowe	H4-62
	S. J. Dechter	R2-50
	C. DeFigh-Price	R2-31
	D. R. Dickinson	L5-31

DISTRIBUTION (cont)

Number of copies

ONSITE

Westinghouse Hanford Company

G. T. Dukelow	R2-32
J. C. Fulton	R2-31
K. A. Gasper	R2-08
J. M. Grigsby	H4-62
H. D. Harmon	R2-52
J. M. Held	R3-12
M. N. Islam	R3-08
J. R. Jewett	T6-50
N. W. Kirch	R2-11
C. A. Kuhlman	B3-30
M. Kummerer	H4-62
J. D. McCormack	L5-31
J. M. McLaren	H0-34
J. E. Meacham (5)	R2-32
N. J. Milliken	H4-62
J. W. Neskas	R2-11
P. M. Phelps	B3-30
D. N. Price	R2-14
F. R. Reich	L5-63
B. C. Simpson	R2-12
S. R. Tiff	H6-16
H. Toffer	H0-38
W. P. Whiting	B3-25
J. C. Wiborg	H4-60
W. D. Winkelman	L5-55
W. F. Zuroff	R2-14
Central Files	L8-04
Document Processing and Distribution (2)	L8-15
EDMC	H6-08
Information Release Administration (3)	R1-08
TFIC	R1-20

This page intentionally left blank.

**DATE
FILMED**

10 / 12 / 93

END